



SPECIFICATION SHEET FOR 0.6" 270K STRAND

PC Strand to ASTM A416

Strand size	0.6" 270K Low Relaxation	
Nominal Strand Diameter	0.600"	15.24 mm
Minimum Breaking Strength	58,600 lbf	260.7 kN/26,580 kgf
Minimum Yield Point At 1% Extension	52,740 lbf	234.6 kN/23,922 kgf
Minimum Elongation In 24" Gauge Length	3.5%	
Minimum Diameter Difference C/W and O/W	0.004 in	0.11 mm
Nominal Modulus Of Elasticity*	28.5 x 10 ⁶ PSI	195.2 kN/mm ² 19,900 kg/mm ²
Nominal Area	0.217 in ²	140.00 mm ²
Nominal Strand Pitch	8.07 in	205 mm
Straightness Max*	1" over 4 ft	25 mm over 1200 mm
Length Per Full Pack*	8,985 ft	2,740 M
Nominal Weight	740 lbs/1,000 ft	1102 kg/1,000 M

*Not Specified by ASTM A416

SUMIDEN WIRE PRODUCTS CORPORATION

East Coast Manufacturing: 710 Marshall Stuart Drive • Dickson, TN 37055 • 615-446-3199 • Fax 615-740-1518
West Coast Manufacturing: 1412 El Pinal Drive • Stockton, CA 95205 • 209-466-8924 • Fax 209-941-2990

PC Sales: • Region: AK, HI & Western Exports – Jeff Feitler, V.P. Sales/Mktg 866-491-5020 • Region: Western U.S. – Glen Gallamore, Reg. Sales Mgr. 503-547-4273

• Region: Eastern U.S. – Steve Koch, Reg. Sales Mgr. 336-940-6652 • Region: Upper Midwest – Andy Ross/Bob Scheel, Sales Rep. 630-719-1687

PC Sales Customer Service: Toll Free 866-491-5020 • Fax 615-446-8188 • East – Charlene Harris • West – Karen Davis